

2019 YEAR END PROMOTION

MobileFiltration Unit

MFU-10

MFU-15



The MobileFiltration unit MFU is used as a portable service unit for filling hydraulic system, flushing small hydraulic systems and for cleaning in bypass flow. Solid particle contamination as well as free water can be removed by the filter element

Technical data

General data	MFU-S	MFU-P
Flow rate, maximum	15 l/min	10 l/min
Pump type	Vane pump	
Operating pressure, maximum	4.0 bar	
Permitted suction pressure at suction port	-0.4 bar to 0.5 bar	
Viscosity range	5 to 650 mm ² /s	5 to 200 mm ² /s
Length of connection cable	3 m (including male connector)	
Length of signal cable (for standard type)	10 m	-
Permitted fluid temperature range	-10 to 80 °C	
Permitted ambient temperature range	-10 to 40 °C	
Seal material	FKM (FPM, Viton®)	
Weight when empty	≈ 17 kg	≈ 16.5 kg

S = Standard (with signal cable for "device in operation")
 P = Premium (with Condition Monitoring)



Promotion Package 1: Standard

Standard MFU-S, 240V, 50Hz, 1Ph - 15L/min
with Signal Cable

- + 1 set of Suction / Pressure Hose with Threaded Connections
- + 5 µm Water Absorbing Filter Element

Promotion Package 2: Premium

Premium MFU-P, 240V, 50Hz, 1Ph - 10L/min
with OnBoard Particle Counter

- + 1 set of Suction / Pressure Hose with Threaded Connections
- + 5 µm Water Absorbing Filter Element

Package 1: Standard MFU-S

List Price: ~~\$4,971.20~~

**30%
DISCOUNT!**

PROMOTION PRICE:

\$ 3,479.80*

Package 2: Premium MFU-P

List Price: ~~\$13,162.20~~

**40%
DISCOUNT!**

PROMOTION PRICE:

\$ 7,897.30*

* Promotion Prices exclude GST and valid for any orders placed from now until 24/12/2019.
 Delivery is currently 2 to 3 days ex-stock Melbourne subject to prior sales!